

JAIIA

ΕN



Manufacturer JAMA Mining Machines AB
Machine type Charging Truck Horizontal (CTH)

Carrier Volvo FMX 4x4

CE markt.

Approved in accordance with AFS 2008:3

Approved in accordance with EN 280 (mobile working

platforms)

DIMENSIONS

 Height [mm]
 3200

 Wheelbase [mm]
 4000/4900

 Length in transport mode [mm]
 9150/10150

BOOM SYSTEM Folding model charging boom.

Electric and diesel operation of boom.

Parallelisation of the basket via the control system.

Basket tilt ±30°

Cable ladder for hose and electric cable on boom.

24V emergency retraction extension boom

CHARGING BASKET Stainless steel charging basket with open profiles.

Approved protective roof. Dual handles for ascent.

Storage boxes in basket (stainless) according to approved

layout.

Approved lifting point for lifting stuff pump.

Winsch for stuff pump - Option*

Max load: Two (2) persons incl equipment = 300 kg Emergency lowering of boom from basket and on carrier.

ELECTRICAL SYSTEM 1000V (660/690V Option*)

Cable reel with rack in stainless steel.

Capacity: 180 meters (max outer diameter of cable 30 mm)
Control of cable reel in cab and in front of carrier

(in/out and automatic roll up)

Cable are not included

Encapsulated transformer 1000/400V 25kVA 1 pc 400V outlet, 16A intended for stuff pump 1 pc 400V outlet, 10A for charging module All electrical cabinets in stainless steel.

Electrical system cont.

Separate 230V supply for interior heater outlet/

battery charging during storage.

Emergency stop 4 pcs (automatic reset of emergency stop)

Cable management in front of carrier (multichassi)

Cable management over roof (long chassi)

Hydraulic power station - Option*

Extra camera for cable reel (separate display in cab) -

Option*

LIGHTING (24V)

Headlamp high beam

Headlamp low beam

Work lights

See technical specification carrier

See technical specification carrier

LED work lighting on boom (2 pcs)

LED ramp on basket LED reverse light (2 pcs)

LED side lighting (2 pcs in front of carrier)

Warning lights Flashlight front and rear

HYDRAULIC SYSTEM

Electro-hydraulic power pack: **

Electric motor 1pc 30kW, efficiency class IE3 enl IEC 60034-2-1

Voltage 660/690/1000V

Hydraulic tank 200 litres

Hydraulic pump Variable piston pump, power regulated

Diesel hydraulic power pack: Engine mounted hydraulic pump VP95

Hydraulic pump Variable piston pump, power regulated

Oil cleaning - Option*

Compressor Option*

FIRE EXTINGUISHING SYSTEM In accordance with SBF-127/Gramko

Sprinkler system Dafo Forrex SV-K100 CO² i 1000/690/660V electrical cabinet.

Two handheld fire extinguishers on chassi (6 kg).

One fire extinguisher in cab (2 kg). Optional brands by agreement*

CENTRAL LUBRICATION Brand "Lincoln" (alternative brands by agreement)

MANUALS 1x Operators Manual and Spare Parts List.

1x Hydraulic diagram and list of components

1x Electric circuit diagrams

2x Digital copies

ADAPTATIONS ON CARRIER Mudguards rear axle in plastic/stainless/galvanized

Cabinet for pentyl stubine

Cabinet for primer

CE MARKT In accordance with the Machinery Directive

2006/42/EG, SS-EN-ISO19296:2019

We reserve the right to make changes as the product is under continuous development. Products must be used in conformity with safe practice, the manufacturers instructions, laws and regulations concerning occupational safety and other recommendations.

Rev. C



^{*} For complete information, please contact the manufacturer or the manufacturer's representative.

^{**} Electric power can be excluded.