





Mobile elevating working platform (MEWP) BK008/SL009 is together with Jama-modified versions Volvo wheel loader L70, L90 and L120 F *, certified and approved for lifting persons. The platform can be operated either from the cabin or from the platform.

Technical data BK008

Platform size L= 2,0m W=2,3m

Complies with the following AFS 2008:03 (Machinery Directive 2006/42/EG)

norms and regulations SS-EN 280:2013 SS-EN 60204:1

SS-EN-4413:2010 AS 1418.10

 L70
 L90
 L120

 Min floor height (A)
 950mm
 950mm

 Max floor height (B)
 4980mm
 4980mm
 5140mm

 Lifting capacity **
 750kg
 1000kg
 1000kg

^{* =} the Wheel Loader must be equipped with 3:rd/4:th hydraulic function and joy-stick steering (CDC control)

^{** =} the weight of operator(s) and options will reduce the working load

Available options BK008 *

Hydraulic powered compressor 1000 l/m 12 bar, weight 80kg

Hydraulic powered generator 5.3 kW incl. two 220V outlets and one 400V outlet, weight 57kg

Hydraulic powered concrete pump, weight 160kg

Canopy for two persons, movable horizontally and vertically (hydraulic function), weight 150kg

Crash bar, weight 57kg

Floor, Galvanized steel grating or Aluminium checker plate

Rock bolt holder and box for washers

Technical data SL009

Platform size L= 1,5m W=1,5m

Canopy Standard

Alternative material Stainless steel with open profiles for corrosive applications, i.e. charging

Complies with the following AFS 2008:03 (Machinery Directive 2006/42/EG)

norms and regulations SS-EN 280 +A2:2009

SS-EN 60204:1 SS-EN-4413:2010

L70 L90

Min floor height (A) * 950mm 950mm

Max floor height (B) * 4980mm 4980mm

Lifting capacity * 750kg 1000kg

We reserve the right to make changes as the product is under continuous development. Products must be used in conformity with safe practice, the manufacturers instructions, laws and regulations concerning occupational safety and other recommendations.

Rev:2017-12-21



^{*} For complete information about available options, please contact the manufacturer or the manufacturer's representative

^{*} Lifting height and lifting capacity may vary depending on the configuration of the lifting arms